PECEIVED CENTRAL FAX CENTER SEP 2 8 2009

Appl. No. 10/587,640 Amdt. Dated June 26, 2009 Reply to Office Action of December 26, 2008

Amendments to the Claims:

This listing will replace all prior versious, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Currently amended): A method for producing an acrylic copolymer, which comprises emulsion polymerizing a monomer mixture of (a) 30-70% by weight of perfluoroalkylalkyl (meth)acrylate, represented by the following general formula:

CH2=CRCOOR'Rf

(where R is a hydrogen atom or a methyl group. R' is a linear or branched alkylene group having 1-8 carbon atoms, and Rf is a perfluoroalkyl group having 4-16 carbon atoms), (b) 25-60% by weight of stearyl (meth)acrylate, (c) 0.1-5% by weight of (meth)acrylamide, and (d) 0.1-5% by weight of N-methylol (meth)acrylamide in the presence of a non-ionic and/or cationic surfactant, wherein at least one of polypropylene glycol, a polypropylene glycol-terminated monomethyl ether and a propylene glycol adduct of glycerine, each a polypropylene glycol-based compound having a molecular weight of 250-5,000 is used as an emulsification aid.

Claim 2 (Previously presented): A method of producing an acrylic copolymer according to Claim 1, wherein after the monomer mixture is emulsified and dispersed by an emulsification means using a

Appl. No. 10/587,640 Amdt. Dated June 26, 2009

Reply to Office Action of December 26, 2008

high pressure homogenizer, a colloid mill or an ultrasonic dispersing apparatus, the emulsion polymerization is carried out by adding a polymerization initiator thereto.

BHGL

Claim 3 (Previously presented): An emulsion polymerized acrylic copolymer produced by a method according to Claim 1.

Claim 4 (Previously presented): A water and oil repellent, which comprises an emulsion polymerized acrylic copolymer according to Claim 3.

Claim 5 (Previously presented): An emulsion polymerized acrylic copolymer produced by a method according to Claim 2.

Claim 6 (Previously presented): A water and oil repellent, which comprises an emulsion polymerized acrylic copolymer according to Claim 5.